

## **BAB 6**

### **Kesimpulan dan Saran**

#### **6.1 Kesimpulan**

Pada penelitian ini digunakan metode optimasi menggunakan PSO dalam mendapatkan nilai koefisien kompresibilitas, koefisien kemiringan permeabilitas dan koefisien permeabilitas awal untuk mendapatkan nilai koefisien konsolidasi yang bervariasi selama waktu terjadinya proses konsolidasi.

Metode Optimasi digunakan untuk menggantikan metode grafis untuk menentukan parameter konsolidasi. Dengan metode Optimasi, parameter konsolidasi yang didapatkan bervariasi dibandingkan dengan metode Taylor dan Casagrande. Hasil back analisis menunjukan bahwa parameter yang digunakan dari hasil optimasi lebih mendekati hasil laboratorium dibandingkan dengan metode Taylor dan Casagrande.

#### **6.2 Saran**

Saran dari penulis adalah penelitian ini membutuhkan data laboratorium yang banyak agar dapat menvalidasi hasil akhir pada simulasi. Penambahan pengujian ini agar dapat memastikan bahwa hasil metode ini dapat diterima pada segala jenis tanah.

## Daftar Pustaka

- Abbasi, N., Rahimi, H., Javadi, A. A., & Fakher, A. (2007). Finite difference approach for consolidation with variable compressibility and permeability. *Computers and Geotechnics*, 34(1), 41–52. <https://doi.org/10.1016/j.compgeo.2006.09.003>
- Abee, W. V. (1986). The influence of bentonite on the permeability of sandy silts. *Nuclear and Chemical Waste Management*, 6(1), 81–88. [https://doi.org/10.1016/0191-815X\(86\)90091-4](https://doi.org/10.1016/0191-815X(86)90091-4)
- Ansari, Y., Merifield, R., & Sheng, D. (2014). A piezocone dissipation test interpretation method for hydraulic conductivity of soft clays. *Soils and Foundations*, 54(6), 1104–1116. <https://doi.org/10.1016/j.sandf.2014.11.006>
- Asaoka, A. (1977). Observational Procedure of Settlement Prediction. *Chemical Pharmaceutical Bulletin*, 57(534), 364–370. <http://www.mendeley.com/research/geology-volcanic-history-eruptive-style-yakedake-volcano-group-central-japan/>
- ASTMD2435-04. (2016). Standard method of test for one-dimensional consolidation properties of soils. *American Association of State Highway and Transportation Officials*, 1–21.
- Bharat, T. V., & Sharma, J. (2011). Prediction of Compression and Permeability Characteristics of Mine Tailings Using Natural Computation and Large-Strain Consolidation Framework. *Geo-Frontiers*, 1081–1090.
- Casagrande, A. (1948). *Die Araometer-Methode zur Bestimmung der Korn . verteilung von Boden und anderen Materialien*.
- Chai, J., Sheng, D., Carter, J. P., & Zhu, H. (2012). Coefficient of consolidation from non-standard piezocone dissipation curves. *Computers and Geotechnics*, 41, 13–22. <https://doi.org/10.1016/j.compgeo.2011.11.005>

Dienstmann, G., Schnaid, F., Maghous, S., & DeJong, J. (2018). Piezocone Penetration Rate Effects in Transient Gold Tailings. *Journal of Geotechnical and Geoenvironmental Engineering*, 144(2), 04017116. [https://doi.org/10.1061/\(asce\)gt.1943-5606.0001822](https://doi.org/10.1061/(asce)gt.1943-5606.0001822)

Dobak, P., & Gaszyński, J. (2014). Evaluation of soil permeability from consolidation analysis based on terzaghi's and biot's theories. *Geological Quarterly*, 59(2), 373–381. <https://doi.org/10.7306/gq.1197>

G. Mesri, T. W. Feng, M. S. (1999). COEFFICIENT OF CONSOLIDATION BY INFLECTION POINT METHOD. *Journal of Geotechnical and Geoenvironmental Engineer- Ing*, 125(8), 716–718.

García-Ros, G., & Alhama, I. (2020). Method to determine the constitutive permeability parameters of non-linear consolidation models by means of the oedometer test. *Mathematics*, 8(12), 1–19. <https://doi.org/10.3390/math8122237>

Haupt, R. L., & Haupt, S. E. (2004). Introduction to optimization. *Optimization of Structural and Mechanical Systems*, 1–34. [https://doi.org/10.1142/9789812779670\\_0001](https://doi.org/10.1142/9789812779670_0001)

Horpibulsuk, S., Yangsukkaseam, N., Chinkulkijniwat, A., & Du, Y. J. (2011). Compressibility and permeability of Bangkok clay compared with kaolinite and bentonite. *Applied Clay Science*, 52(1–2), 150–159. <https://doi.org/10.1016/j.clay.2011.02.014>

Ishibashi, I., & Hazarika, H. (2015). Soil mechanics fundamentals and applications, second edition. In *Soil Mechanics Fundamentals and Applications, Second Edition*.

Kaniraj, S. R., & Gayathri, V. (2004). Permeability and Consolidation Characteristics of Compacted Fly Ash. *Journal of Energy Engineering*, 130(1), 18–43. [https://doi.org/10.1061/\(asce\)0733-9402\(2004\)130:1\(18\)](https://doi.org/10.1061/(asce)0733-9402(2004)130:1(18))

- Lakkoju, V., Kommu, S., Madhusudhan Reddy, M., Sony, B., & Asadi, S. S. (2020). In-situ consolidation analysis by asaoka and hyperbola methods. *International Journal of Scientific and Technology Research*, 9(2), 6296–6302.
- Lekha, K. R., Krishnaswamy, N. R., & Basak, P. (2003). and Compressibility. *Water Resources, November*, 1001–1009.
- Leroueil, S. (1988). Tenth Canadian geotechnical colloquium: recent developments in consolidation of natural clays. *Canadian Geotechnical Journal*, 25(1), 85–107. <https://doi.org/10.1139/t88-010>
- Lim, Y. X., Tan, S. A., & Phoon, K. K. (2019). Interpretation of horizontal permeability from piezocone dissipation tests in soft clays. *Computers and Geotechnics*, 107(November 2017), 189–200. <https://doi.org/10.1016/j.compgeo.2018.12.001>
- Lun, P. T. W., & Parkin, A. K. (1985). Consolidation behaviour determined by the velocity method. *Canadian Geotechnical Journal*, 22(2), 158–165. <https://doi.org/10.1139/t85-022>
- Mersi, G., & Godlewak, P. M. (1977). *Compressibility , swelling and consolidation. April 1976*, 774051.
- Nogami, T., & Li, M. (2003). Consolidation of Clay with a System of Vertical and Horizontal Drains. *Journal of Geotechnical and Geoenvironmental Engineering*, 129(9), 838–848. [https://doi.org/10.1061/\(asce\)1090-0241\(2003\)129:9\(838\)](https://doi.org/10.1061/(asce)1090-0241(2003)129:9(838))
- Olek, B. S. (2019). Critical Reappraisal of Casagrande and Taylor Methods for Coefficient of Consolidation. *KSCE Journal of Civil Engineering*, 23(9), 3818–3830. <https://doi.org/10.1007/s12205-019-1222-8>
- Olek, B. S. (2020). Experimental insights into consolidation rates during one-dimensional loading with special reference to excess pore water pressure. *Acta Geotechnica*, 15(12), 3571–3591. <https://doi.org/10.1007/s11440-020-01042-3>

- Pane, V., Croce, P., Znidarcic, D., Ko, H. Y., Olsen, H. W., & Schiffman, R. L. (1983). Effects of consolidation on permeability measurements for soft clay. *Geotechnique*, 33(1), 67–72. <https://doi.org/10.1680/geot.1983.33.1.67>
- Parkin, A. K. (1990). Coefficient of consolidation by the velocity method. *Water Resources Research*, 905138–905138.
- Proskin, S., Sego, D., & Alostaz, M. (2010). Freeze-thaw and consolidation tests on Suncor mature fine tailings (MFT). *Cold Regions Science and Technology*, 63(3), 110–120. <https://doi.org/10.1016/j.coldregions.2010.05.007>
- Robinson, R. G. (1997). Consolidation analysis by an inflection point method. *Geotechnique*, 47(1), 199–200. <https://doi.org/10.1680/geot.1997.47.1.199>
- Sahab, M. G., Toropov, V. V., & Gandomi, A. H. (2013). A Review on Traditional and Modern Structural Optimization: Problems and Techniques. In *Metaheuristic Applications in Structures and Infrastructures* (First Edit). Elsevier Inc. <https://doi.org/10.1016/B978-0-12-398364-0.00002-4>
- Shivaram, B., & K. Swamee, P. (1977). A computational method for consolidation coefficient. *Chem. Pharm. Bull.*, 40(6), 1569–1572.
- Shukla, S. K., Sivakugan, N., & Das, B. M. (2009). Methods for determination of the coefficient of consolidation and field observations of time rate of settlement - An overview. *International Journal of Geotechnical Engineering*, 3(1), 89–108. <https://doi.org/10.3328/IJGE.2009.03.01.89-108>
- Silveira, M. V., Calheiros, A. V., & Casagrande, M. D. T. (2018). Applicability of the Expanded Polystyrene as a Soil Improvement Tool. *Journal of Materials in Civil Engineering*, 30(6), 06018006. [https://doi.org/10.1061/\(asce\)mt.1943-5533.0002276](https://doi.org/10.1061/(asce)mt.1943-5533.0002276)
- Sridharan, A., Murthy, N. S., & Prakash, K. (1988). Rectangular hyperbola method of

consolidation analysis. *Geotechnique*, 38(3), 467–473.  
<https://doi.org/10.1680/geot.1988.38.3.467>

Taylor, D. W. (1948). Fundamentals of soil mechanics. In *Geotechnical, Geological and Earthquake Engineering* (Vol. 36, pp. 45–59). [https://doi.org/10.1007/978-94-017-9460-2\\_4](https://doi.org/10.1007/978-94-017-9460-2_4)

Terzaghi, C. (1929). *SETTLEMENT OF BUILDINGS DUE TO PROGRESSIVE CONSOLIDATION OF INDIVIDUAL STRATA*. 266–292.

Terzaghi, K. (1943). Theoretical Soil Mechanics. *Theoretical Soil Mechanics*.  
<https://doi.org/10.1002/9780470172766>

Tiwari, B., & Ajmera, B. (2012). New Correlation Equations for Compression Index of Remolded Clays. *Journal of Geotechnical and Geoenvironmental Engineering*, 138(6), 757–762. [https://doi.org/10.1061/\(asce\)gt.1943-5606.0000639](https://doi.org/10.1061/(asce)gt.1943-5606.0000639)

Wang, M. C., & Huang, C. C. (1985). *Soil compaction and permeability prediction model*. 110(6), 1063–1083.

Yin, J. H., & Feng, W. Q. (2017). A new simplified method and its verification for calculation of consolidation settlement of a clayey soil with creep. *Canadian Geotechnical Journal*, 54(3), 333–347. <https://doi.org/10.1139/cgj-2015-0290>

Zeng, L. L., Hong, Z. S., & Han, J. (2018). Experimental investigations on discrepancy in consolidation degrees with deformation and pore pressure variations of natural clays. *Applied Clay Science*, 152(October), 38–43.  
<https://doi.org/10.1016/j.clay.2017.10.029>